

SL 13,500LB

12V STEEL OR SYNTHETIC



13,500LB (6, 123KG) SL SERIES ORIGINAL ORANGE 12V ELECTRIC WINCH, TWIN WIRELESS REMOTE CONTROL.
IDEAL FOR EQUIPMENT HAULERS, FLATDECKS, RECOVERY TRUCKS AND 4X4S UP TO 3.5T

FEATURES

- > 13,500LB (6, 123KG) STRAIGHT-LINE PULL SL SERIES 12V ELECTRIC WINCH.
- > LATEST TECHNOLOGY LONG-RANGE COMBINATION WIRELESS REMOTE CONTROLS, TWIN HANDSETS.
- > SUPER POWERFUL 12V 6.8HP/5.1KW SERIES WOUND ELECTRIC MOTOR.
- > MASSIVE ULTRA-TOUGH THREE-STAGE GEARBOX WITH HARDENED STEEL GEARS.
- > MOTOR AND GEARBOX CASING MACHINED FROM BILLET STEEL FOR MAXIMUM IMPACT PROTECTION.
- > 24M (79FT) X 9.5MM MULTI-STRAND STEEL WIRE ROPE. 28M (92FT) X 11MM DIAMETER SYNTHETIC ROPE.
- > NEW THROUGH-DRUM ROPE CONNECTION WITH GRUB SCREW CLAMP FOR ULTRA-SECURE ROPE ATTACHMENT TO DRUM.
- > CLEVIS HOOK WITH SAFETY CATCH AND HAND SAVER. 3/8 INCH G70 GRADE FORGED. ZINC PLATED FOR CORROSION RESISTANCE.
- > TOUGH FOUR ROLLER FAIRLEAD WITH ZINC PLATED ROLLERS.
- > HEAVY-DUTY ONE-PIECE SOLENOID, LATEST DESIGN, ULTRA-RELIABLE, IP67 WATERPROOF.
- > POWER IN/OUT BIG GRIP HANDHELD UNIT.
- > SLIDING RING GEAR FREEWHEEL CLUTCH.
- > HIGH TENSILE FIXING BOLT KIT.
- > STRONG WINCHMAX BRANDED COVER TO PROTECT FROM WATER AND ROAD GRIME.
- > HEAVY-DUTY & BUILT TO LAST - GROSS WEIGHT 40KG.
- > CE CERTIFIED & BUILT TO ISO9001 QUALITY MANAGEMENT SYSTEM REQUIREMENTS.

UPCOMING MODELS WILL ALSO INCLUDE:

- FITTED CABLE TENSIONER.
- BATTERY ISOLATOR.
- AUXILIARY CONTROL TAILS INSIDE CONTROL BOX PRE-INSTALLED TO SOLENOID WITH FEMALE O.180" FOR ADDITIONAL CUSTOM WIRELESS REMOTE APPLICATIONS.
- 90 DEGREE M8 CRIMP TERMINAL WITH HEAT SHRINK SUPPLIED LOOSE.

LAYER RATED	LINE PULL (LB/KG)		TOTAL ROPE ON DRUM (FT/M)	
1	13,500	6,123	20.4	6.22
2	9,530	4,332	41	12.0
3	7,929	3,604	71	21.0
4	6,770	3,077	85	24.0

LINE PULL (LB/KG)		LINE SPEED FT/MIN (M/MIN)		MOTOR (AMPS)
0	0	24.6FT	7.5M	70A
3,000	1,363	11.48FT	3.5M	138A
6,000	2,727	8.86FT	2.7M	218A
9,000	4,090	7.72FT	2.2M	260A
13,500	6,123	5.58FT	1.7M	350A

SPECS

SINGLE LINE RATED PULL	13,500LB (6,123KG)
MOTOR	12V 6.8HP/5.1KW SERIES WOUND
CONTROL	2 - BIG GRIP REMOTE SWITCHES, 4.5M LEAD
GEAR TRAIN	3 STAGE PLANETARY
GEAR REDUCTION RATIO	265:1
CLUTCH	SLIDING RING GEAR
BRAKING ACTION	AUTOMATIC IN THE DRUM
DRUM SIZE	DIAMETER 64MM (2.5") LENGTH 224MM (8.82")
DRUM FINISH	BLACK, PAINTED.
WIRE CABLE (STANDARD)	24M (79FT) X 9.5MM (3/8") DIAMETER STEEL WIRE ROPE
SYNTHETIC ROPE (STANDARD)	28M (92FT) X 11MM DIAMETER SYNTHETIC ROPE
HOOK	CLEVIS HOOK WITH SAFETY CATCH, ZINC PLATED.
FAIRLEAD	4-WAY ROLLER FAIRLEAD
BATTERY	RECOMMENDED 650CCA MINIMUM FOR WINCHING
BATTERYLEADS	2 GAUGE, 1.83M (72") 25MMSQ - 5.6MM DIAMETER
WINCH FINISH	ORIGINAL ORANGE POWDER COATED
WEIGHT (GW)	CABLE VERSION ESTIMATED 40KG. (88LB) SYNTHETIC VERSION ESTIMATED 30KG. (66 LBS)
OVERALL DIMENSIONS (LXWXH)	536 X 160 X 218MM (21.3" X 6.3" X 8.6")
MOUNTING BOLT PATTERN (STANDARD)	10.00" ±0.015" X 4.50" ±0.010" (254 X 114.3MM)
MOTOR CURRENT	65-500A
NO LOAD LINE SPEED	7.5M/MIN (24.6 FT/MIN)
WATERPROOF	IP67 RATING

