

SL5,000LB

12V STEEL OR SYNTHETIC



5,000LB (2,268KG) ORIGINAL ORANGE 'SL SERIES' 12V ELECTRIC WINCH, STEEL OR SYNTHETIC ROPE, TWIN WIRELESS REMOTE CONTROL. IDEAL FOR USE ON BOAT TRAILERS, ATVS, AND LIGHT UTILITY VEHICLES.

FEATURES

- > 5,000LB (2,268KG) STRAIGHT-LINE PULL 12V ELECTRIC WINCH
- > LATEST TECHNOLOGY LONG-RANGE WIRELESS REMOTE CONTROLS, TWIN HANDSETS
- > POWERFUL 12V 1.5HP PERMANENT MAGNETIC MOTOR
- > ULTRA-TOUGH THREE-STAGE PLANETARY GEARBOX WITH HARDENED STEEL GEARS
- > CHOICE OF 15.2M X 6.3MM GALVANIZED STEEL WIRE ROPE OR 15.2M X 6.3MM DYNEEMA SK75 SYNTHETIC ROPE
- > NEW THROUGH-DRUM ROPE CONNECTION WITH GRUB SCREW CLAMP FOR ULTRA-SECURE ROPE ATTACHMENT TO DRUM
- > 1/4 INCH G70 GRADE FORGED CLEVIS HOOK WITH SAFETY CATCH AND HAND SAVER, ZINC PLATED FOR CORROSION RESISTANCE
- > FAIRLEAD: FOUR-ROLLER WITH ZINC PLATED ROLLERS (STEEL) / PRECISION CNC-MILLED ALUMINIUM HAWSE (SYNTHETIC)
- > HEAVY-DUTY ONE-PIECE SOLENOID, LATEST DESIGN, IP67 WATERPROOF RATED
- > POWER IN/OUT ROCKER SWITCH WITH HANDLEBAR MOUNT INCLUDED
- > FREE-SPOOL CLUTCH FOR FAST ROPE PAYOUT
- > HIGH TENSILE MOUNTING BOLT KIT
- > SUPPLIED WITH 2X 180CM BATTERY POWER CABLES AND 2X 90CM MOTOR POWER CABLES
- > STRONG WINCHMAX BRANDED COVER TO PROTECT FROM WATER AND ROAD GRIME
- > CE CERTIFIED & BUILT TO ISO9001 QUALITY MANAGEMENT SYSTEM REQUIREMENTS

LAYER RATED	LINE PULL (LB/KG)	
1	5,000	2,268
2	4,080	1,851
3	3,450	1,565
4	2,985	1,354

LINE PULL (LB/KG)		LINE SPEED FT/MIN (M/MIN)		MOTOR (AMPS)
0	0	20.5FT	6.2M	20A
1,250	567	13.1FT	4.0M	77A
2,500	1,134	11.8FT	3.6M	124A
3,750	1,700	9.2FT	2.8M	188A
5,000	2,268	4.9FT	1.5M	286A

SPECS

SINGLE LINE RATED PULL	5,000LB (2,268KG)
MOTOR	12V 1.5HP PERMANENT MAGNETIC MOTOR
CONTROL	TWIN WIRELESS REMOTE IN/OUT + HANDLEBAR-MOUNTED ROCKER SWITCH
GEAR TRAIN	3 STAGE PLANETARY
GEAR REDUCTION RATIO	166:1
CLUTCH	CAM ACTIVATED FREE SPOOL
BRAKING ACTION	AUTOMATIC FULL LOAD HOLD
DRUM FINISH	STEEL - PAINTED BLACK
WIRE CABLE (STANDARD)	15.2M (50FT) X 6.3MM GALVANIZED STEEL WIRE ROPE
SYNTHETIC ROPE (STANDARD)	15.2M (50FT) X 6.3MM DYNEEMA SK75 SYNTHETIC ROPE
HOOK	CLEVIS HOOK 1/4 INCH, ZINC PLATED
FAIRLEAD	4-WAY ROLLER FAIRLEAD (STEEL VERSION) / CNC-MILLED ALUMINIUM HAWSE FAIRLEAD (SYNTHETIC VERSION)
BATTERY	RECOMMENDED 12AH MINIMUM FOR WINCHING
BATTERY LEADS (X2)	10MM ² X 180CM
MOTOR LEADS (X2)	10MM ² X 90CM
WINCH FINISH	ORIGINAL ORANGE POWDER COATED
WEIGHT (GW)	CABLE VERSION ESTIMATED 16.2KG (35.7 LBS) / SYNTHETIC VERSION ESTIMATED 13.6KG (29.9 LBS)
OVERALL DIMENSIONS (LXWXH)	390 X 120 X 117MM (15.4" X 4.7" X 4.6")
MOTOR CURRENT	15-296A
NO LOAD LINE SPEED	6.2M/MIN (20.5 FT/MIN)
WATERPROOF	IP67 RATING

